













Unified Network Storage

• General

- 2U / 12 bay form factor
- Intel Xeon Quad-core 2.66.GHz processor
- 16 GB ECC Memory
- Two 10/100/1000 Ethernet ports with load balancing and failover
- Two 10 Gigabit Ethernet ports with load balancing and failover (SFP+ ports)
- 2 USB 2.0 ports

Software

- NETGEAR ReadyDATA OS 1.0 using ZFS
- Setup using easy browser-based dashboard

Scalability

 Supports up to two EDA4000 – 4U/24-bay expansion chassis

• RAID

- Multiple volume support for RAID 0, 1, 5, 6, 10
- Instant Provisioning / Instant expansion
- Hot swappable disks
- Hot spare disk support
- SSD performance boost

Advanced Data Management for Shares and LUNs

- Unlimited Snapshots
- Compression and De-duplication
- Thick and Thin Provisioning

Network Protocols

- CIFS/SMB for Windows
- AFP 3.3 for Mac OS 9/X
- NFS v2/v3 for Linux and UNIX
- HTTP/S for web browsers
- FTP/S
- IPv6
- SNMP
- iSCSI target support for Windows, Mac and UNIX/Linux initiators

User Security and Data Access

- Local users and Active Directory/ Windows Domain support
- Secure Sockets Layer (SSL)
- CHAP authentication for iSCSI LUN
- Shares

Network Services

- DHCP or static IP address assignment
- NTP server synchronization
- LACP support for load balancing and failover
- Virtual Network Interface Card (vNIC)
 - 1. VLAN Access
 - 2. IP Settings
 - 3. Performance throttling

System Management

- Performance tuning options
- Device health status
- System configuration backup and restore
- Email alerts and event logs
- SNMP

Backup and DR Options

- Hourly, Daily, Weekly scheduled snapshots (Data Protection)
- Cloud managed Constant Replication (Disaster Recovery)
- Client backup target using CIFS, NFS, FTP or iSCSI
- Supported Backup applications from Acronis, Quest, StorageCraft, Symantec, VEEAM

Supported Web Browsers

- Internet Explorer 7.0+
- Opera 9.5+; Safari 2.0+
- Mozilla Firefox® 3.0+

Languages

- Management UI: English, German, French, Chinese, Japanese
- File names: Unicode

• Electrical

- PSU: 2 x 700W server-rated AC power supply
- Input: 100 240V AC, 50/60 Hz

Power Consumption

- 290W typical (with 12 x 1 TB disks)

• Thermal

- 3* 80 mm dual ball-bearing chassis cooling fans
- Fan failure alert
- High temperature email alert with auto-shutdown option

Operating Environment

- 0° 40° C
- 20% 80% humidity (non-condensing)
- FCC, CCC, C-Tick, KCC, VCCI, RoHS compliance

• Physical

- Form factor: 2U rack-mount with 12 hot-swappable SATA/SAS drive bays
- Dimensions: (h x w x d) —
 89 x 437 x 648 (mm)
 3.5 x 17.2 x 25.5 (in)
- Weight: 32.8 kg (76 lb) with 12 disks

• Warranty

- NETGEAR 5-year Warranty*
- Next business day onsite hardware replacement support, 3 years (included)**

ProSupport Service Packs Available

- PMB0334 OnCall 24x7, Category 4, 3 Years
- PMB0354 OnCall 24x7, Category 4, 5 Years
- PSB 0304-10000S Professional Setup and Configuration (Remote)
- PSP 1104-10000S Professional Setup and Configuration (Onsite)

NETGEAR[°]

350 E. Plumeria Drive San Jose, CA 95134-1911 USA 1-888-NETGEAR (638-4327) E-mail: info@NETGEAR.com www.NETGEAR.com NETGEAR, the NETGEAR logo, Connect with Innovation, ReadyDATA, are trademarks and/or registered trademarks of NETGEAR, Inc. and/or its subsidiaries in the United States and/or other countries. Other brand names mentioned herein are for identification purposes only and may be trademarks of their respective holder(s). Information is subject to change without notice. © 2012 NETGEAR, Inc. All rights reserved.

This product comes with a limited warranty, the acceptance of which is a condition of sale.

*Basic technical support provided for 90 days from date of purchase.

**See http://onsite.netgear.com for coverage, availability and terms and conditions.