




### Take Gigabit to the Desktop

### Features and Highlights

- 16 or 24 ports deliver up to 2000Mbps of dedicated, non-blocking bandwidth per port
- Instant Plug-N-Play connectivity with Auto-negotiation and Auto MDI/MDI-X
- Easily combine new or existing 10-, 100- and 1000Mbps devices within your network
- 802.1p QoS support for prioritizing voice and video in the network
- Jumbo Frame Support up to 9KB
- Each port delivers up to 2000Mbps of network speed (full duplex)
- Fast, auto-switching and auto-sensing 10/100/1000Mbps Ethernet connection
- 16 or 24 switched ports provide bandwidth for PCs, servers or switches
- Auto Uplink™ automatically adjusts for straight-through or crossover cables
- Plug and play—begins working as soon as it is powered on
- Integrates 10-,100- and 1000Mbps devices into your network
- Compact size for desktop or for mounting in a standard 19-inch rack
- Secure, durable metal housing includes a Kensington locking slot for theft prevention
- Backed by a NETGEAR Limited Lifetime\* Warranty
- Honors TOS/802.1p prioritization
- Up to 50% lower power consumption\*\*
- Auto power-down mode saves energy when port is unused
- Auto green mode detects cable length and adjusts power usage to save energy
- Packaging manufactured with at least 80% recycled materials



# 16- and 24-port Gigabit Ethernet Switches

Network Ports	JGS516	JGS524
Multicast Groups	16 10/100/1000Mbps Ethernet RJ-45 ports	24 10/100/1000Mbps Ethernet RJ-45 ports
<b>Performance Specifications</b>		
Switching bandwidth	32Gbps	48Gbps
Forwarding Rate	10 Mbps port: 14,880 frames/sec 100 Mbps port: 148,800 frames/sec 1000 Mbps port: 1,488,000 frames/sec	
Latency (using 64 byte packets)	10Mbps: 35µs (max) 100Mbps: 30µs (max) 1000Mbps: 15µs (max)	
RAM buffer	256KB	
MAC address database	8K	
Mean time between failures (MTBF)	441,123 hours	238,872 hours
Power Consumption	11.8W max	17.9W max
Power Cord	100-240V; 50-60Hz; plug is localized to country of sale	
Jumbo Frame Support	up to 9KB	
<b>Standards Compliance</b>		
IEEE 802.3i 10BASE-T Ethernet	IEEE 802.3x flow control	
IEEE 802.3u 100BASE-TX Fast Ethernet	IEEE 802.3 CAMA/CD	
IEEE 802.3ab 1000BASE-T Gigabit Ethernet	IEEE 802.3az Energy Efficient Ethernet	
<b>Status LEDs</b>		
Unit	Power	
Per network port	Link, activity, speed	
<b>Physical Specifications</b>		
Dimensions (w x d x h)	328 x 169 x 43mm (12.9 x 6.7 x 1.7in)	
Weight	1.47kg (3.24lb)	1.65kg (3.64lb)
<b>Environmental Specifications</b>		
Operating temperature	32° to 122°F (0° to 50°C)	
Operating humidity	90% maximum relative humidity, non-condensing	
Storage temperature	-4° to 158°F (-20° to 70°C)	
Storage humidity	10 to 95% relative humidity	
<b>Electromagnetic Emissions</b>		
Certifications	CE Class A, including EN 55022 (CISPR 22) and EN 55024 FCC Part 15 Class A VCCI Class A C-Tick Class A KCC CCC	

<b>Safety Agency Approvals</b>	
Certifications	UL (UL 60950-1)/ cUL CE LVD (EN 60950-1) CB KCC CCC RU EAC
<b>System Requirements</b>	
	UTP Category 5 cables or better Network software (e.g., Windows <sup>®</sup> , Mac <sup>®</sup> OS, Linux)
<b>Warranty</b>	
	NETGEAR Limited Lifetime* Warranty
<b>ProSupport Service Packs Available</b>	
OnCall 24x7, Category 1	PMB0331-100 (US) PMB0331 (non-US)
<b>Package Contents</b>	
All models	16- or 24-port Gigabit Ethernet Switch (JGS516v2 or JGS524v2) Power cord Installation guide Rackmount kit Warranty/support information card
<b>Ordering Information</b>	
<b>JGS516</b>	
JGS516NA	North America
JGS516-200EUS	Europe
JGS516AU	Asia
JGS516-300JPS	Japan
<b>JGS524</b>	
JGS524NA	North America
JGS524-200EUS	Europe
JGS524AU	Asia
JGS524-300JPS	Japan
JGS524-200PRS	China

\* This product comes with a limited warranty that is valid only if purchased from a NETGEAR authorized reseller, and covers unmodified hardware, fans and internal power supplies - not software or external power supplies, and requires product registration at <https://www.netgear.com/business/registration> within 90 days of purchase; see <https://www.netgear.com/about/warranty> for details. Intended for indoor use only.

\*\* Maximum power savings when compared to previous version of this NETGEAR product.

NETGEAR, the NETGEAR Logo, and NETGEAR Insight are trademarks of NETGEAR, Inc. in the United States and/or other countries. Other brand names mentioned herein are for identification purposes only and may be trademarks of their respective holder(s).

NETGEAR, Inc. 350 E. Plumeria Drive, San Jose, CA 95134-1911 USA, 1-888-NETGEAR (638-4327), E-mail: [info@NETGEAR.com](mailto:info@NETGEAR.com), [www.NETGEAR.com](http://www.NETGEAR.com)